

Finned Tube Heaters **RiRo-V4A**

high-grade stainless steel 1.4571



For most demanding appliances and with highest resistance against corrosion we also offer our RiRo heaters in high-grade stainless steel V4A, type 1.4571. Produced identically to the standard types, all steel parts are made of V4A and pickling ensures a long service life.

Typical applications are sewage plants, offshore platforms or swimming facilities.



universal --RiRo-u

Power W	Voltage V	Length mm	Weight kg	Order number
500	230 V	440	3,1	U 0500EA4
1000	230/400 V	640	4,6	U 1000EA4
1500	230/400 V	840	6,1	U 1500EA4
2000	230/400 V	1040	7,7	U 2000EA4
3000	230/400 V	1440	10,6	U 3000EA4
4000	400 V	1840	13,7	U 4000EA4
5000	400 V	2240	17,0	U 5000EA4
6000	400 V	2640	19,7	U 6000EA4

automatic - RiRo-a

Power W	Voltage V	Length mm	Weight kg	Order number
500	230 V	440	3,1	A 0500EA4
1000	230 V	640	4,6	A 1000EA4
1500	230 V	840	6,1	A 1500EA4
2000	230 V	1040	7,7	A 2000EA4
3000	230 V	1440	10,6	A 3000EA4

step switch - RiRo-s

Power W	Voltage V	Length mm	Weight kg	Order number
1000	230 V	640	4,7	S 1000EA4
1500	230 V	840	6,1	S 1500EA4
2000	230 V	1040	7,7	S 2000EA4
3000	230 V	1440	10,6	S 3000EA4



Special voltage
290 / 500 V 3(N)~

Finned Tube Heaters

Special mains voltage 290/500V (universal)

Power requirements of special voltages are quite usual in industrial and commercial areas as well as in foreign countries. Therefore we offer suitable solutions with short delivery times. Below you can find heaters for most common situations. Please contact us for your special requirement!



SNS 290/500 V Hight 170mm Widh 130mm Diameter \varnothing 110 mm Prot. Mode IP 66 / IP 67

Type	Power W	Length mm	Weight kg	Order number
u 1000 500V	1000	640	4,6	SNS017
u 1500 500V	1500	840	6,1	SNS124
u 2000 500V	2000	1040	7,7	SNS030
u 3000 500V	3000	1440	10,9	SNS005
u 4000 500V	4000	1840	13,7	SNS046
u 5000 500V	5000	2240	17,0	SNS045
u 6000 500V	6000	2640	19,7	SNS024



 SELV 42V

Finned Tube Heaters

42 V safety extra-low voltage



SELV 42V Hight 170mm Widh 130mm Diameter \varnothing 110 mm Prot. Mode IP 66 / IP 67

Type	Power W	Length mm	Weight kg	Order number
u 250 42V	250	440	3,1	SKS005
u 500 42V	500	440	3,1	SKS006
u 750 42V	750	640	4,6	SKS007
u 1000 42V	1000	640	4,6	SKS010