

Finned Tube Heaters **RiRo-u** universal



The versatile

This line covers a large variety of situations with standard heaters ranging from 500W to 6,000 W. Like our other heaters they are corrosion-proof (high grade steel type 1.4512). Our insulation provides the highest measure of electric safety (dust-proof and water-proof, rated IP 66/67). Heaters are equipped with cable gland M20 for the safe and easy use of cables up to H07RN-F5G1,5.

In the range from 1,000W to 3,000W you can choose your connection to be either 230V or 400V 3 (N). Heaters with layout for special voltages can easily be provided, too, as well as with different grades of steel, for example for food industry or offshore appliances. Please see page RiRo-V4A for further information. A multitude of solutions for your special needs is possible: Schultze-RiRo heaters perfectly work with external thermostats as well as any other sort of control.

RiRo-u

Suitable accessories, page 17+18



max. 240°C Hight 170mm Widh 130mm Diameter Ø 110mm Prot. Mode IP66/IP67

Power W	Voltage V	Length mm	Weight kg	Order number
500	230 V \cong	440	3,1	U 0500E
1000	230 V \cong 400 V 3 \sim 400 V 3 N \sim	640	4,6	U 1000E
1500		840	6,1	U 1500E
2000		1040	7,5	U 2000E
3000	400 V 3 \sim 400 V 3 N \sim	1440	10,6	U 3000E
4000		1840	13,7	U 4000E
5000		2240	17,0	U 5000E
6000		2640	19,7	U 6000E

High grade stainless steel type 1.4512. Also available: Type 1.4571



Finned Tube Heaters **RiRo-s** with built-in step switch

With the built-in three step switch heating power can be adjusted according to actual requirements.

This helps saving energy!

Step I 1/3 of heating power

Step II 2/3 of heating power

Step III full heating power



Suitable accessories, page 17+18



max. 240°C Hight 170mm Widh 130mm Diameter Ø110mm Prot. Mode IP66/IP67

Power W with 230 V~	Length mm	Weight kg	Order number
1000	640	4,6	S 1000E
1500	840	6,1	S 1500E
2000	1040	7,5	S 2000E
3000	1440	10,8	S 3000E

High grade stainless steel type 1.4512. Also available: Type 1.4571



Finned Tube Heaters **RiRo-a** with built-in thermostat

The heating power is steplessly adjustable and the thermostat keeps your chosen temperature constant. Choose either frost protection or your temperature between + 5°C and + 30°C. The red signalling light shows when power is on.

● = frost-free ◡ = + 5° C to + 30° C



Suitable accessories, page 17+18



Adjustable + 5° C to + 30° C

max. 240°C Hight 170mm Widh 130mm Diameter Ø110mm Prot. Mode IP66/IP67

Power W with 230 V~	Length mm	Weight kg	Order number
500	440	3,1	A 0500E
1000	640	4,6	A 1000E
1500	840	6,1	A 1500E
2000	1040	7,7	A 2000E
3000	1440	10,8	A 3000E

High grade stainless steel type 1.4512. Also available: Type 1.4571